



The F series speakers are suitable for all applications where highly precise and broadband sound transmission down to low frequencies is required. This makes perfect integration easy and opens up many application possibilities in the field of corporate events, trade fairs and product presentations, press conferences, in conference rooms and lecture halls, in theaters, concert halls and cinemas as well as in sports halls and fitness centers. If the speakers are supported by subwoofers, concert levels are also possible. The arrangement of the components ensures good focusing to optimize speech intelligibility. All models feature newly developed top-class components to achieve the best possible sound quality and defined dispersion characteristics.

PRODUCT SPECIFICATIONS


Speaker Components	2 x 6,5" Nd (2,5" VC) / 1" Nd (1,7" VC)
Description	Fullrange Speaker System
Power AES / Peak	600 W / 1800 W
Impedance nominal	8 Ω
SPL 1 W / Peak @ 1 m	92,5 dB / 125 dB
Usable Range	65 Hz - 20 kHz (-6 dB)
Tuning Frequency Excursion minimum	65 Hz
X - Overpoint acoustical	1,1 kHz
Coverage horizontal / vertical	90° x 60°, rotatable
Enclosure Wedge Angle	20°
Connectors	2 x NLT4MP in/out (optionally NLT4FP) Coding: 1 +/- FR, 2 +/- loop thru
Handles	1 x
Rigging / Fittings	8 x M10 / 2 x M6 35 mm pole mount
Weight	12,5 kg
Size height x width x depth	52,0 x 21,0 x 30,0 cm
Order No.	00315




The tweeter horn can be rotated by 90° as required.




The front grille is held in place by magnets and is easy to remove.



DIMENSIONS




8 x M10 Twinpoints for MultiRigg™




MEASUREMENTS


2D Directivity Plot - horizontal




2D Directivity Plot - vertical



Frequency Response with Preset + Impedance



Flying-Bracket



for F 2, horizontal alignment,
(incl. 4 x socket head screws
M10 x 20 mm)

Order No. **01207/F2**

Handle Screw



for flying brackets, adjustable,
M10 x 20 mm

Order No. **08375/20**

MultiRigg™



for flown and ground stacked
applications, (incl. 2 x knurled screws
M10 x 20 mm, 1 x handle screw
M8 x 55 mm), max. load 50 kg

Order No. **01360**

MultiRigg™ Light



for fixed installations,
(incl. 2 x socket head screws M10 x
20 mm), max. load 50 kg

Order No. **01362**

MultiRigg™ Basic



(incl. load adapter M10,
2 x knurled screws M10 x 20 mm),
max. load: 50 kg

Order No. **01364**

MultiTilt™



Tilt adapter with adjustable tilt
from 0° to 37,5° (2,5° steps),
integr. pole mount adapter with clam-
ping device, (incl. 2 x knurled screws
M10 x 20 mm), max. load 50 kg

Order No. **01370**

Knurled Screw



M10 x 20 mm

Order No. **73750/w** (RAL 9010)

Order No. **73750**

Pole Mount Adapter



35 mm Ø → M10 x 16 mm,
M8 x 20 star knob screw

Order No. **08126**

35 mm Ø → M10 x 16 mm

Order No. **08126/II**

Knurled Head Nut



reduction screw for fastening
M10 Pole Mount Adapter (08126)

Order No. **73755**

Flange



with ball and socket joint,
with additional locking screw,
M10 x 15 mm, max. load 15 kg

Order No. **08125**

Quick Trigger Clamp - small



M10, max. load 20 kg

Order No. **01223/20 kg**

Quick Trigger Clamp



max. load 100 kg

Order No. **01223/100 kg**

Truss Clamp



incl. M10 mini TV spigot,
max. load 15 kg

Order No. **01221**

Steel Safety



6 mm x 600 mm, black,
quick connector undetachably,
max. load 22 kg (BGI 810-3)

Order No. **01376/6**

Ring Screw



M10— DIN 580

Order No. **73700** (zincd)

Order No. **73700/sw** (black zincd)

TV Spigot



M10 internal thread,
28 mm Ø

Order No. **08128**

ACCESSORIES F 2

Wall Mount



ball and socket joint flange (08125)
+ 08125/plate
Order No. **08125/set**

Wall Mount



bar: 269 mm, max. load 40 kg,
(incl. socket head screw M10 x 70 mm,
hex lock nut and flat washer M10)
Order No. **08130/F/269/w** (RAL 9010)
Order No. **08130/F/269**

Wall Mount



bar: 400 mm, max. load 40 kg,
(incl. socket head screw M10 x 70 mm,
hex lock nut and flat washer M10)
Order No. **08130/F/400/w** (RAL 9010)
Order No. **08130/F/400**

Wall Mount



for permanent installation,
incl. tilt angle stop,
M10, max. load 15 kg
Order No. **08131/F/w** (RAL 9010)
Order No. **08131/F**

Wall Mount



2 x M6 fixing holes (d=73 mm),
1 x M10 fixing hole (center),
max. load 25 kg
Order No. **03034/w** (RAL 9010)
Order No. **03034**

Wall Mount



using fixing points d= 73 mm
Order No. **08132/w** (RAL 9010)
Order No. **08132**

Bag



for 1 x F 2, with two-way zip,
padded, incl. label pocket
Order No. **01224/F2**

Flight Case Trunk



for 2 pcs. F 2,
accessory compartment, 20,5 cm wide,
with mounting option for MultiRigg /
MultiTilt, heavy duty, 9 mm birch mul-
tiplex, PVC coated black, 6 x recessed
sprung handles, 1 x butterfly latch
medium, 4 x stacking recesses,
4 x 100 mm blue wheels (2 pcs. with
brake), interior lined with felt, 27 kg
Size: 53 x 60 x 71,5 cm (W x D x H)
Order No. **16105**

